
		Reolink Innovation Limited		K2K4GPTSM64-UK	
Picture					
Camera	Video & Audio	Image Sensor	1/3" CMOS Sensor		
		Video Resolution	2560 x 1440 (4Megapixels)@15FPS		
		Video Format	H.265		
		Lens	f = 2.8mm fixed, F1.6		
		Field of View	Horizontal: 95°, Vertical: 57°, Diagonal : 115°		
		Infrared Night Vision	Up to 10 Meters (33ft) (LED: 12pcs/14mil/940nm)		
		Digital Zoom	16x digital zoom		
	Audio	Two-way audio			
	PIR Detection & Alerts	Smart Alarm	PIR Detection/Human Detection/Animal Detection		
		PIR Detecting Distance	Adjustable up to 10m (33 ft)		
		PIR Detecting Angle	120° horizontal		
		Audio Alert	Customized verbal alerts		
		Recording	Motion Triggered Recording		
	Other Alerts	Instant email alerts and push notifications			
	3G/4G	Frequency Bands	Europe	LTE FDD: B1/B3/B5/B7/B8/B20 WCDMA: B1/B5/B8	
			America	LTE FDD: B2/B4/B12 WCDMA: B2/B4/B5	
			Australia	LTE FDD: B1/B2/B3/B4/B5/B7/B8/B28 LTE TDD: B40 WCDMA: B1/B2/B5/B8	
		Transmission Data	LTE FDD: Max 10Mbps(DL), Max 5Mbps(UL)		
			LTE TDD: Max 8.96Mbps(DL), Max 3.1Mbps(UL)		
	HSPA+: Max 42Mbps(DL), Max 5.76Mbps(UL) UMTS: Max 384Kbps(DL), Max 384Kbps(UL)				
	Other Features	Add Markers	Yes		
	Power	Battery	6000mAh rechargeable battery (Battery life varies based on settings, usage & temperature)		
		Solar	Reolink Solar Panel		
DC Power		5V/2A USB power adaptor			
Storage	Local Storage	Supports up to 128GB micro SD card(Included 64GB microSD Card)			
	Cloud Storage	Supports Reolink Cloud			
Smart Home	Work with	Google Assistant			
Working Environment	Operating Temperature	-10 to 55° C (14° to 131° F)			
	Waterproof	Support			
Size & Weight	Dimension	Φ98 x 112mm (Φ3.7 x 4.4 in)			
	Weight (Battery included)	485 g (17. 1 oz)			
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/			
Solar Panel	Electrical Parameters	Max Voltage	6.0V		
		Max Current	530mA		
		Max Power	3.2W		
	Size & Weight	Dimensions	185.4x120.4x6.5(mm)		
		Cable Length	4 meters (157.48in)		
		Weight	280g (9.9oz)		
		Interface	Micro USB Port		
	Other Parameters	Working Temperature	- 10°C to 55°C (14°F to 131°F)		
		Working Humidity	10%~90%		
		Weather Resistance	IP65		
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/			