


camera	Picture			
	Video & Audio	Image Sensor	1/2.7" CMOS Sensor	
		Video Resolution	UP To: 3840 x 2160 (8 Megapixels) at 15 frames/sec	
		Lens	F=2.8mm@ F=1.6 , f=8mm@ F=1.6	
		Video Format	H.264, H.265	
		Field of View	Horizontal : 105° Vertical : 55°	
		Zoom Mode	10X hybrid zoom	
		Day & Night	IR-cut filter with auto-switching	
		Infrared Night Vision	Up to 10 Meters (33ft)(LED: 6pcs/850nm)	
		Color Night Vision	Spotlight: 2pcs/6500K/	
		Audio	Two-way Audio	
	Power	Battery	6000mAh rechargeable battery ( Battery life varies based on settings, usage & temperature)	
		Solar	Reolink Solar Panel 2	
		DC Power	5V/2A	
	Interface	Power	USB Type-C port	
		System	Reset Button	
		Storage	Supports up to 128GB micro SD card(Included 64GB microSD Card)	
		Audio	Built-in Microphone and Speaker	
	Wi-Fi	Wi-Fi Standard	IEEE 802.11a/b/g/n	
		Operating Frequency	2.4GHz/5GHz	
		Wi-Fi Security	WPA-PSK/WPA2-PSK	
	Software Features	Frame Rate	Main Stream: 10fps - 15fps Sub Stream: 10fps - 15fps	
		Code Rate	Main Stream: 1024Kbps -2048Kbps	
		OS Supported	PC: Windows, Mac OS; Smart phone: iOS, Android	
		Smart Alarm	PIR Detection/ Human Detection/Vehicle Detection/ Pet Detection	
		Record Mode	Motion Triggered Recording	
		Protocols & Standards	SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P	
Maximal User Access		Support up to 12 simultaneous video streams ( 10 substreams & 2 main streams)		
Work with		Google Assistant, Reolink Cloud		
Working Environment	Temperature	Operating Temperature: -10°C~+55°C		
	Humidity	Operating Humidity: 20% ~ 85%		
	Waterproof	Support		
Size & Weight	Dimension	127*80*56mm		
	Weight	335g		
Warranty	Limited Warranty	2-year limited warranty. For support, visit <a href="https://support.reolink.com/hc/en-us/">https://support.reolink.com/hc/en-us/</a>		
Solar Panel	Electrical Parameters	Max Voltage	6.0V	
		Max Current	960mA	
		Max Power	5.8W	
	Size & Weight	Dimensions	185.4x120.4x6.5(mm)	
		Cable Length	210.6 x 174.6 x 15.4 (mm)	
		Weight	4 meters	
		Interface	USB Type-C Port	
	Other Parameters	Working Temperature	-10°C to 55°C (14°F to 131°F)	
		Working Humidity	10%~90%	
		Weather Resistance	IP65	
Warranty	Limited Warranty	2-year limited warranty. For support, visit <a href="https://support_reolink.com/hc/en-us/">https://support_reolink.com/hc/en-us/</a>		