

Picture



Video & Audio

Image Sensor	1/2.7" CMOS Sensor
Video Resolution	Default: 2560X1920 (5 megapixels) @20FPS
Lens	f=2.26mm F=2.0, with IR cut
Video Format	H.264
Field of View	Horizontal: 134°
	Vertical: 97°
	Diagonal: 180°
Pre-Motion Recording	Support
Audio	Two-way audio, Noise reduction, Echo Suppression
Quick Replies	Support

Power

Hardwired	12-24VAC 50/60Hz, DC 24V
-----------	--------------------------

Interfaces

Power	Power port
System	Reset button
Ethernet	One 10M/ 100Mbps RJ45
Storage	Micro SD card slot (Max. 256GB), Reolink NVR
Audio	Built-in 2 Microphones & Speaker

WiFi

Wireless Standard	IEEE 802. 11a/b/g/n
Operating Frequency	2.4GHz/5GHz
Wireless Security	WPA-PSK/WPA2 -PSK

Software

Frame Rate	Mainstream: 2fps - 20fps (default: 20fps)
	Substream: 4fps - 15fps (default: 10fps)
Code Rate	Mainstream: 1024Kbps - 6144Kbps (default: 4096Kbps)
	Substream: 64Kbps - 512Kbps (default: 256Kbps)
Browsers Supported	Edge, Chrome, Firefox, Safari
OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
Smart Alarm	Motion detection/Person detection/Vistor detection
Recording Modes	Motion recording (default)/scheduled recording
Protocols & Standards	HTTPS, IPv4, UPNP, RTSP, RTMP, ONVIF, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P
Work with	Google Assistant&Alexa
Rich Notification	Support

Working Environment

Temperature	Operating temperature: - 10°C~+55°C ( 14°F~ 131°F)
Humidity	Operating humidity: 10% ~ 90%
Waterproof	Support

Size & Weight

Dimension	133mm(H)x48mm(W)x23mm(T)
Weight	96g

Warranty

Limited Warranty	2-year limited warranty. For support, visit <a href="https://support.reolink.com/hc/en-us/">https://support.reolink.com/hc/en-us/</a> .
------------------	---