

## Picture



<b>Camera</b>	<b>Video &amp; Audio</b>	Image Sensor	1/3" CMOS Sensor	
		Video Resolution	2560 x 1440 (4.0Megapixel) at 15 frames/sec	
		Video Format	H.265	
		Field of View	Fixed lens, Horizontal: 95°, Vertical: 57°, 115° diagonal	
		Infrared Night Vision	up to 10 Meters (33ft) (LED: 6pcs/14mil/850nm)	
		Digital Zoom	16x digital zoom	
		Audio	Two-way audio	
	<b>PIR Detection &amp; Alerts</b>	Smart Alarm	PIR detection/Human Detection/Vehicle Detection	
		PIR Detecting Distance	Adjustable up to 10m (33 ft)	
		PIR Detecting Angle	120° horizontal	
		Audio Alert	Customized verbal alerts	
		Recording	Motion Triggered Recording	
		Other Alerts	Instant email alerts and push notifications	
	<b>3G/4G</b>	Frequency Bands	Europe	LTE FDD: B1/B3/B5/B7/B8/B20 WCDMA: B1/B5/B8
			America	LTE FDD: B2/B4/B12 WCDMA: B2/B4/B5
			Australia	LTE FDD: B1/B2/B3/B4/B5/B7/B8/B28 LTE TDD: B40 WCDMA: B1/B2/B5/B8
		Transmission Data	LTE FDD: Max 10Mbps(DL), Max 5Mbps(UL)	
			LTE TDD: Max 8.96Mbps(DL), Max 3.1Mbps(UL)	
			HSPA+: Max 42Mbps(DL), Max 5.76Mbps(UL)	
			UMTS: Max 384Kbps(DL), Max 384Kbps(UL)	
	<b>Power</b>	Battery	6000mAh rechargeable battery (Battery life varies based on settings, usage & temperature)	
		Solar	Reolink Solar Panel	
		DC Power	5V/2A USB power adaptor	
	<b>Storage</b>	Local Storage	Supports up to 128GB micro SD card(Included 64GB microSD Card)	
		Cloud Storage	Supports Reolink Cloud	
	<b>Smart Home</b>	Smart Home	Works with Google Assistant	
	<b>Working Environment</b>	Operating Temperature	- 10 to 55° C ( 14° to 131° F)	
Weather Resistance		IP64 Weatherproof		
<b>Size &amp; Weight</b>	Size	Φ98 x 1 12mm (Φ3.7 x 4.4 in)		
	Weight (Battery included)	485 g ( 17. 1 oz)		
<b>Warranty</b>	Limited Warranty	2-year limited warranty. For support, visit <a href="https://support.reolink.com/hc/en-us/">https://support.reolink.com/hc/en-us/</a>		
<b>Solar Panel</b>	<b>Electrical Parameters</b>	Max Voltage	6.0V	
		Max Current	530mA	
		Max Power	3.2W	
	<b>Size &amp; Weight</b>	Dimensions	185.4x120.4x6.5(mm)	
		Cable Length	4 meters (157.48in)	
		Weight	280g (9.9oz)	
		Interface	Micro USB Port	
	<b>Other Parameters</b>	Working Temperature	- 10°C to 55°C (14°F to 131°F)	
		Working Humidity	10%~90%	
		Weather Resistance	IP65	
	<b>Warranty</b>	Limited Warranty	2-year limited warranty. For support, visit <a href="https://support.reolink.com/hc/en-us/">https://support.reolink.com/hc/en-us/</a>	