
GUIDELINES FOR WORKTOP SURFACE PROTECTION FILM

Please read before using this product

USAGE

1. **Protects** against spills, scratches, stains & dirt during building works, remodeling, painting, decoration and furniture removal
2. Heavy duty rip-resistant material
3. **Self-adhesive makes it quick and easy** to apply and remove
4. This protection film is to be used as temporary surface protection against dust, paint, plaster and potential scratching. This is not designed for protection against corrosion, humidity or chemicals.

APPLICATION

1. Before applying the film ensure the surface is clean and dry.
2. It is recommended to test the product on small area of the surface prior to using. Test the film for 48 hours on a small hidden area of surface to ensure compatibility with the surface and to ensure that there is no adhesive transfer or damage to surface.
3. Do not store or use above 37°C or below 4°C. The product should be stored at room temperature 24 hours prior to application.
4. To apply the roll, lay it on the work surface facing the direction required to cover. Push the roll forward a small distance and press down firmly to ensure the film has adhered to the hard surface.
5. Continue to unroll, pressing down and smoothing out any air pockets, checking the film is rolled straight.

LIMITATIONS

1. **Do not leave the film in place for longer than 30 days.**
2. The film can be stored for up to six months in its original packaging at room temperature and in dry conditions.
3. For use on **hard surface only**.
4. Do not use on **glass or carpets**.
5. Film is **single** use only. Remove and dispose of in accordance with local environmental regulations.
6. **CAUTION!** May cause damage to varnished surfaces where the curing process had not finished. Please give sufficient time for varnish to fully adhere to the surface prior to applying the film.
7. **Do not apply to a damp surface**, which will prevent any moisture from evaporating and could

cause discoloration and may affect the performance of the product.

8. High traffic areas or outdoor exposure may require renewal of film weekly.

9. The product should be applied at room temperature.

10. No responsibility will be taken for the misuse of this product, or the consequences of such non-recommended applications. Use of the product for non-recommended applications is done so at users own risk. Our liability is limited to the cost of or replacement of a defective product and does not cover any claims for consequential losses. It is recommended that the whole surface is covered to avoid dirt distribution.

11. Avoid prolonged periods in direct sunlight.

12. It is recommended that the whole work surface is covered to avoid dirt distribution.